



ATEC C-Valve Dimensions

Pos.	Name	e.g. material	Notice
1	body	316L	
2	cyl. screw	A2-70	
3	c-ball	316L	X
4	stem	318LN	
5	body cover	316L	
6	sealing disc	PEEK	
7	TA-Luft packing	PTFE/Graphite	X
8	pressure ring	316L	
9	belleville spring	301	
10	o-ring	Viton	X
11	sealing ring	PTFE	X
12	seat ring	PTFE	X
13	hxg. screw	A2-70	
14	sealing ring	PTFE	X

Pos.	Name	e.g. material	Notice
15	inlet flange	316L	
16	hxg. screw	A2-70	
17	cyl. screw	A2-70	
18	hxg. screw	A2-70	
19	body stop	316L	
20	lock plate	316L	X
21	cover	316L	
22	body stop ring	316L	
23	o-ring	Viton	X
24	bearing	PEEK	X
25	hand lever	304	
26	bearing	PEEK	X
27	bearing stud	316L	
-	-	-	

x = Verschleißteile

ATEC Anschlussmaße

DN	ØK	ØE	ØG	ØD	ØF	M	H	L	B	AF	A
1"	85	4 x M12	85	4 x 13,5	115	74	37,5	182,5	210	11	F05
2"	125	4 x M16	125	4 x 18,0	165	90	44	238	277,5	14	F07
3"	160	8 x M16	160	8 x 18,0	200	125	61	291	236	17	F07
4"	180	8 x M16	180	8 x 18,0	220	145	72	311	346,5	17	F07

